

PRODUCT SAFETY DATA SHEET

ACCORDING TO 93/112/EC

EP3 GROUT

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY		HARDENER component 2 of 3	
PRODUCT NAME AND CODE: EP3 GROUT - 3201-5		EMERGENCY NUMBER (OFFICE HOURS) 01639 730481	
COMPANY-UNDERTAKING IDENTIFICATION - ROTAFIX HOUSE, ABERCRAF, SWANSEA, SA9 1UR. TEL: 01639 730481 FAX: 01639 730858			
2. COMPOSITION/INFORMATION ON INGREDIENTS			
Chemical characterisation			
Description: Hardener for epoxy resins			
Dangerous components:			
CAS NO.	Designation	%	Index
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	50-100	C
100-51-6	benzyl alcohol	25-<50	Xn
69-72-7	salicylic acid	3-<10	Xn
			R-phrases
			21/22-34-43
			20/22
			22
3. HAZARDS IDENTIFICATION			
Hazard designation: Corrosive			
Information pertaining to particular dangers for man and environment			
R20/21/22 Harmful by inhalation, in contact with skin and if swallowed			
R34 Causes burns			
R43 May cause sensitization by skin contact			
4. FIRST-AID MEASURES			
INHALATION: Remove victim to ventilated area - seek medical attention.			
SKIN: Wash with warm soapy water immediately, remove contaminated clothing.			
EYES: Rinse opened eye with plenty of water for several minutes, seek medical advice.			
INGESTION: Do not induce vomiting. Seek medical advice.			
5. FIRE-FIGHTING MEASURES			
EXTINGUISHANTS LARGE FIRE/SMALL FIRE: Dry powder CO ₂ , water jet, alcohol-resistant foam. Wear breathing apparatus.			
6. ACCIDENTAL RELEASE MEASURES			
Methods for cleaning up: Absorb liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust) and place into containers for disposal. Disposal of containers according to local regulations. Wash spill site thoroughly after material pick-up is complete.			
7. HANDLING AND STORAGE			
HANDLING: Ensure good ventilation. Wear protective equipment.			
STORAGE PRECAUTIONS: Keep in sealed containers of origin. Carbonates on exposure to air.			
8. EXPOSURE CONTROLS/PERSONAL PROTECTION			
RECOMMENDED PROTECTIVE CLOTHING: Safety goggles, overalls and rubber gloves.			
GENERAL PROTECTION AND HYGIENIC MEASURES: Keep away from foodstuffs, beverages and food. Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of work. Avoid contact with eyes and skin.			
9. PHYSICAL & CHEMICAL PROPERTIES:			
PHYSICAL STATE: Liquid		APPEARANCE: clear/light pink/brown	
DENSITY @ 20°C: 1.01 g/cm ³		ODOUR: Ammoniacal	
VAPOUR DENSITY (AIR = 1):		pH: 11	
VAPOUR PRESSURE @ 25°C:		VISCOSITY @ 25°C: 50 mPa.s	
SOLUBLE IN WATER: Partial			
10. STABILITY AND REACTIVITY			
THERMAL DECOMPOSITION/CONDITIONS TO BE AVOIDED: No decomposition if used according to specification.			
DANGEROUS REACTIONS: No dangerous reaction known			
DANGEROUS PRODUCTS OF DECOMPOSITION: no dangerous decomposition products known.			
11. TOXICOLOGICAL INFORMATION			
ACUTE TOXICITY: LD/LC50 values that are relevant for classification:			
Components	Type	Value	Species
benzyl alcohol	oral	1300 mg/kg	rat
	dermal	2000 mg/kg	rbt
Harmful/corrosive: Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of oesophagus and stomach.			
PRIMARY IRRITANT EFFECT:			
ON THE SKIN: Caustic effect on skin and mucous membranes			
ON THE EYE: Strong caustic effect			
SENSITIZATION: sensitization possible by skin contact and inhalation			
12. ECOLOGICAL INFORMATION:			
Hazardous for water. Should not be allowed to enter sewers and water courses.			
13. DISPOSAL CONSIDERATIONS			
Do not allow into drains or water courses. Wastes including emptied containers, are controlled wastes and should be disposed of in accordance with Local and National regulations made under the Control of Pollution Act and the Environmental Protection Act. Using information provided in this data sheet, advice should be obtained from the Waste Regulation Authority whether the special waste regulations apply.			
14. TRANSPORT INFORMATION			
Land transport ADR/RID and GGVS-GGVE (cross-border - domestic)		UN-number: 2289	
ADR/RID - GGVS/E Class: 8 Corrosive materials		label: 8	
Number-letter: 53c			
Kemler number: 80			
designation of goods: ISOPHORONEDIAMINE 50%			
15. REGULATORY INFORMATION			
Designation according to EC guidelines: This product has been classified and labelled in accordance with EC directives. See paragraphs 2, 3, and 8			
16. OTHER			
Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by a work activity using this product is undertaken before this product is used.			
This information contained herein is based on our present knowledge however, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.			

PRODUCT SAFETY DATA SHEET

ACCORDING TO 93/112/EC

EP3 GROUT

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY		Filler Component 3 of 3
PRODUCT NAME AND CODE: EP3 GROUT		EMERGENCY NUMBER (OFFICE HOURS) 01639 730481
COMPANY-UNDERTAKING IDENTIFICATION - ROTAFIX HOUSE, ABERCRAF, SWANSEA, SA9 1UR. TEL: 01639 730481 FAX: 01639 730858		
2. COMPOSITION/INFORMATION ON INGREDIENTS		
NATURE & COMPOSITION: Silica sands, grades of cement and cement modifiers, plasticisers and other cementitious compounds. The lime, calcium silicates and alkalis within the cement are partially soluble and when mixed with water will give rise to a potentially hazardous alkaline solution.		
3. HAZARDS IDENTIFICATION		
Cement mortar and concrete mixes may until set cause both irritant, contact dermatitis due to alkalinity, abrasiveness of the materials or allergic contact dermatitis due to hexavalent chromium slats. On the skin: may cause serious burns and ulceration On the eyes: may cause serious irritation. The eyes are particularly vulnerable and damage with increase with contact time and chemical burns can develop without pain being felt at the time.		
4. FIRST-AID MEASURES		
INHALATION: Leave work area, change clothing. SKIN: Remove contaminated clothing, wash skin with copious amounts of water. If irritation occurs - see medical advice. EYES: Irrigate with clean water for at least 15 minutes, seek medical attention. INGESTION: In the event of ingestion wash mouth with water and seek medical attention.		
5. FIRE-FIGHTING MEASURES Not applicable		
6. ACCIDENTAL RELEASE MEASURES		
Recover the spillage in a dry state if possible, Minimise generation of airborne dust.		
7. HANDLING AND STORAGE		
STORAGE PRECAUTIONS: Store in cool dry area HANDLING: Low toxicity, dry and dusty, contains silica. Wear appropriate particulate mask, when wet will be alkaline and can cause an allergic dermatitic condition to some people.		
8. EXPOSURE CONTROLS/PERSONAL PROTECTION		
RECOMMENDED PROTECTIVE CLOTHING: Suitable respiratory protection should be worn to ensure that personal exposure is less than the Occupational exposure standard. Dust proof goggles/glasses, rubber gloves, overalls, barrier cream. should be worn GENERAL PROTECTION AND HYGIENIC MEASURES: Keep away from foodstuffs, beverages and food. Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of work. Avoid contact with eyes and skin.		
9. PHYSICAL AND CHEMICAL PROPERTIES		
PHYSICAL STATE: Free flowing blended powder	APPEARANCE: Grey	
DENSITY @ 25°C: 1.35-1.40 gms/cc	ODOUR: Nil	
VAPOUR DENSITY (AIR = 1):	pH: part alkaline	
VAPOUR PRESSURE @ 25°C: N/A	VISCOSITY @ 25°C:	
SOLUBLE IN WATER: No		
10. STABILITY AND REACTIVITY		
Hazardous decomposition products: None. Conditions contributing to chemical instability: None		
11. TOXICOLOGICAL INFORMATION Low toxicity, dry and dusty, contains silica. Wear appropriate particulate mask, when wet will be alkaline and can cause an allergic dermatitic condition to some people.		
ACUTE TOXICITY:		
PRIMARY IRRITANT EFFECT:		
ON THE SKIN: Avoid contact with wet material, wear appropriate clothing.		
ON THE EYE: Severe eye irritant. Can lead to soreness and chemical burning. Wear appropriate mask and/or goggles		
INHALATION: may cause inflammation of mucous membranes.		
SENSITIZATION: sensitization possible by skin contact		
12 ECOLOGICAL INFORMATION:		
Aquatic Toxicity Rating LC50 aquatic toxicity rating not determined. The addition of cements to water will, however, cause the pH to rise and may therefore be toxic to aquatic life in some circumstances.		
13. DISPOSAL CONSIDERATIONS		
Do not allow into drains or water courses. Wastes including emptied containers, are controlled wastes and should be disposed of in accordance with Local and National regulations made under the Control of Pollution Act and the Environmental Protection Act. Using information provided in this data sheet, advice should be obtained from the Waste Regulation Authority whether the special waste regulations apply.		
14. TRANSPORT INFORMATION		
Classification for conveyance - not required.		
15. REGULATORY INFORMATION		
Risk Phrases		
Contact with wet product may cause irritation, dermatitis or burns. Contact between product powder and body fluids (e.g. sweat and eye fluid) may also cause irritation, dermatitis or burns. There is a risk of serious damage to eyes.		
Safety Phrases		
Wear suitable protective clothing, gloves and eye/face protection. In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice. After contact with skin, wash immediately with plenty of clean water. Keep out of reach of children.		
16. OTHER INFORMATION		
Customers are urged to ensure that the product is entirely suitable for there own purpose. It is the customers responsibility to ensure that a suitable and sufficient assessment of the risks created by a work activity using this product is undertaken before this product is used. This information contained herein is based on our present knowledge however, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.		